

GENERAL TIRE

2018 ARCA TIRE SPECIFICATIONS

Speedways (12.0/28.0R15)

Charlotte Circumference Air Pressure Outer/Inner	LS TEST	RS TEST	Chicago Circumference Air Pressure Outer/Inner	LS 7219	RS 8568
	87 1/4"	88 5/8"		87 1/4"	88 5/8"
	-----	-----		LF 28/43#	RF 49/64#
				LR 28/43#	RR 46/61#
Daytona Circumference Air Pressure Outer/Inner	LS 7331	RS 8492	Gateway Circumference Air Pressure Outer/Inner	LS TEST	RS TEST
	87 3/4"	88 1/4"		87 1/4"	88 5/8"
	LF 35/50#	RF 55/70#		-----	-----
	LR 35/50#	RR 50/65#			
Iowa Circumference Air Pressure Outer/Inner	LS TEST	RS TEST	Kansas Circumference Air Pressure Outer/Inner	LS 7219	RS 8568
	87 1/4"	88 5/8"		87 1/4"	88 5/8"
	-----	-----		LF 30/45	RF 52/67
				LR 30/45	RR 50/65
Michigan Circumference Air Pressure Outer/Inner	LS 7219	RS 8568	Pocono Circumference Air Pressure Outer/Inner	LS TEST	RS TEST
	87 1/4"	88 5/8"		87 1/4"	88 5/8"
	LF 30/45	RF 52/67		-----	-----
	LR 30/45	RR 50/65			
Talladega Circumference Air Pressure Outer/Inner	LS 7331	RS 8492			
	87 3/4"	88 1/4"			
	LF 35/50#	RF 55/70#			
	LR 35/50#	RR 50/65#			

No less than an additional 15 PSI in Inner Liner.

Short Tracks	11.0/28R15	Radials	No Inner Liners Used at Short Tracks		
Berlin 27L/44R	LF 16#	RF 29#	Elko 27L/44R	LF 18#	RF 32#
	LR 16#	RR 29#		LR 18#	RR 30#
Fairgrounds 27L/44R	LF 18#	RF 32#	LOR 27L/44R	LF 20#	RF 32#
	LR 18#	RR 32#		LR 20#	RR 30#
Madison 27L/44R	LF 18#	RF 36#	Salem 27L/44R	LF 21#	RF 37#
	LR 18#	RR 34#		LR 21#	RR 35#
Toledo 27L/44R	LF 18#	RF 33#			
	LR 18#	RR 31#			
Dirt Tracks	(11.0/88-15)	Bias Tires	Springfield	(11.0/88-15)	Bias Tires
DuQuoin 45L/70R Dirts	LF 18#	RF 24#	45L/70R Dirts	LF 18#	RF 22#
	LR 16#	RR 24#		LR 18#	RR 22#

Nitrogen replacement procedure:

- (1) Deflate outer chamber completely.
- (2) Reduce inner chamber to **no less than 15#**
- (3) Inflate inner to recommended pressure.
- (4) Inflate outer to recommended pressure.

Minimum Recommended Inflation PSI

**All Subject to Change.
Check with General at each Event.**

REV 1/9/18