

## GENERAL TIRE

### 2021 ARCA TIRE SPECIFICATIONS

#### Speedway Codes (12.0/28.0R15)

<b>Bristol</b>	LS	RS	<b>Charlotte</b>	LS	RS	
	<b>1013</b>	<b>2262</b>		<b>7511</b>	<b>8604</b>	
	Circumference	87"		88 1/2"	87 1/4"	88 1/2"
	Air Pressure	LF 22#		RF 44/59#	LF 28/43#	RF 56/71#
Outer/Inner	LR 22#	RR 40/55#	Outer/Inner	LR 29/44#	RR 54/69#	
<b>Daytona</b>	LS	RS	<b>Iowa</b>	LS	RS	
	<b>1229</b>	<b>2380</b>		<b>1013</b>	<b>2262</b>	
	Circumference	87 3/4"		88 1/4"	87"	88 1/2"
	Air Pressure	LF 35/50#		RF 55/70#	LF 18#	RF 36#
Outer/Inner	LR 35/50#	RR 50/65#	Outer	LR 18#	RR 34#	
<b>Kansas</b>	LS	RS	<b>Michigan</b>	LS	RS	
	<b>7511</b>	<b>8604</b>		<b>7511</b>	<b>8604</b>	
	Circumference	87 1/4"		88 1/2"	87 1/4"	88 1/2"
	Air Pressure	LF 30/45#		RF 52/67#	LF 28/43#	RF 54/69#
Outer/Inner	LR 30/45#	RR 50/65#	Outer/Inner	LR 28/43#	RR 50/65#	
<b>Phoenix</b>	LS	RS	<b>Pocono</b>	LS	RS	
	<b>1013</b>	<b>2262</b>		<b>1013</b>	<b>2262</b>	
	Circumference	87"		88 1/2"	87"	88 1/2"
	Air Pressure	LF 18#		RF 35#	LF 23/38#	RF 38/53#
Outer	LR 18#	RR 33#	Outer/Inner	LR 23/38#	RR 36/51#	
<b>Talladega</b>	LS	RS				
	<b>1229</b>	<b>2380</b>				
	Circumference	87 3/4"	88 1/4"			
	Air Pressure	LF 35/50#	RF 55/70#			
Outer/Inner	LR 35/50#	RR 50/65#				

Inner Liner cold inflation should be at least 15 PSI above the cold tire inflation.

Road Course	11.0/28R15	Radials	Road Course	12.0/28R15	Radials
Circumference-88 3/4"			Circumference-88 1/2"		
<b>Mid-Ohio</b>	LF 28#	RF 28#	<b>Watkins Glen</b>	LF 31#	RF 29#
Tire Code 44	LR 25#	RR 25#	Tire Code 2124	LR 25#	RR 25#

11.0/28R15	Radials	No Inner Liners Used			
Circumference-Left Side 87 1/2" Right Side 88 3/4"					
<b>Berlin</b> 27L/44R	LF 16#	RF 29#	<b>Elko</b> 27L/44R	LF 16#	RF 32#
	LR 16#	RR 29#		LR 16#	RR 30#
<b>Milwaukee</b> 27L/44R	LF 18#	RF 30#	<b>Salem</b> 27L/44R	LF 21#	RF 37#
	LR 18#	RR 30#		LR 21#	RR 35#
<b>Toledo</b> 27L/44R	LF 18#	RF 33#			
	LR 18#	RR 31#			

Dirt Tracks	(11.0/88-15)	Bias Ply			
<b>DuQuoin</b> 45L/70R Dirts	LF 18#	RF 24#	<b>Springfield</b> 45L/70R Dirts	LF 18#	RF 22#
	LR 16#	RR 24#		LR 18#	RR 22#

#### Nitrogen replacement procedure:

- (1) Deflate outer chamber completely.
- (2) Reduce inner chamber to **no less than 15#**
- (3) Inflate inner to recommended pressure.
- (4) Inflate outer to recommended pressure.

**All Pressures are COLD Starting Recommended.**

**All Subject to Change.**

**Check with General Tire at each Event.**

REV 1/5/21